## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: SIMPEX Basic

Supplier's address: SIMPEX Import Export GmbH , Europastraße 3, 5015 Salzburg, AT

Model identifier: 28721

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	DLS		
Light source cap-type	GU5.3				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	Nein		
Colour-tuneable light source:	Nein	Envelope:	-		
High luminance light source:	Nein				
Anti-glare shield:	Nein	Dimmable:	Yes		
Product parameters					

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
•.	mption in on- 100 h), rounded 1st integer	5	Energy efficiency class	F		
indicating if it r in a sphere (3	us flux (фuse), refers to the flux 60º), in a wide in a narrow cone	345 in Narrow cone (90°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 700		
On-mode   expressed in W	oower (P <sub>on</sub> ),	4,4	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00		
for CLS, expre	ndby power (P <sub>net</sub> ) ssed in W and second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set	80		
Outer	Height	46	Spectral power	See image		
dimensions	Width	50	distribution in the	in last page		
without	Depth	50	1	Seite 1 / 3		

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load					
Claim of equivalent power <sup>(a)</sup>	Ja	If yes, equivalent power (W)	35				
		Chromaticity coordinates (x and y)	0,458 0,410				
Parameters for directional light sources:							
Peak luminous intensity (cd)	700	Beam angle in degrees, or the range of beam angles that can be set	36				
Parameters for LED and OLED light sources:							
R9 colour rendering index value	0	Survival factor	0,90				
the lumen maintenance factor	0,95						

(a)'-' : not applicable;

(b)<sub>'-'</sub> : not applicable;

